

L106P PERFORMA CHRONOMETRIC AUTOMATIC WATER SOFTENER



AUTOTROL VALVE
268/740 LOGIX



WATER CONNECTION
3/4\"G - 1\"G



MIXER



TECNICAL FEATURES

Weight		85 kg
Power supply		230V50/60 Hz
	optional	120V 60 Hz
Max flow rate suggested		4000 l/h
Water connection		3/4\"G-1\"G
Salt quantity for regeneration cycle		15.8 kg
Room temperature		min 4°C – max 35°C
Salt refill		100 kg

INFEEED WATER FEATURES

Drinkable water	
Clear water (SDI 1)	
Temperature	Min 6° C Max 25°C
Infeed water pressure	Min 2 bar Max 8 bar
Max water hardness	90°f

THE SOFTENER IS COMPOSED OF

- 1 Brine tank 150 litres
- 1 268/740 Logix Autotrol Valve
- 1 Vessel 13\" x 54\" with 74.2 litres cationic resins adapt for softening
- 1 Instruction manual
- 4 Metres of unloading pipe
- 1 Overflow curved union joint
- 1 Drain connection
- 1 Resin disinfection kit (OPTIONAL)

THE SOFTENER IS SUITABLE FOR

- Centralized water net for bars and kitchens

PRODUCT CODE:

- L10603P Coupling 1\"G
- L10605P Coupling 3/4\"G

LITRES OF SOFT WATER BASED ON WATER HARDNESS						
°f	20	30	40	50	60	Cyclic Capacity m ³ .°f
°d	11	16	22	28	33	
ppm CaCO ₃	200	300	400	500	600	
L106P	22260	14840	11130	8904	7420	445.2

