

L24P PERFORMA CHRONOMETRIC AUTOMATIC WATER SOFTENER



AUTOTROL VALVE
268/740 LOGIX



WATER CONNECTION
3/4"G - 1"G



MIXER



TECNICAL FEATURES

Weight		22kg
Power supply		230V50/60 Hz
	optional	120V 60 Hz
Max flow rate suggested		4000 l/h
Water connectin		3/4G"-1"G
Salt quantity for regeneration cycle		2.7 kg
Room temperature		min 4°C – max 35°C
Salt refill		75 kg

THE SOFTENER IS COMPOSED OF

- 1 Brine tank 100 litres
- 1 268/740 Logix Autotrol Valve
- 1 Vessel 8" x 35" with 16.8 litres cationic resins adapt for softening
- 1 Instruction manual
- 4 Metres of unloading pipe
- 1 Overflow curved union joint
- 1 Drain connection
- 1 Resin disinfection kit (OPTIONAL)

INFEEED WATER FEATURES

Drinkable water	
Clear water (SDI 1)	
Temperature	Min 6° C Max 25°C
Infed water pressure	Min 2 bar Max 8 bar
Max water hardness	90°f

THE SOFTENER IS SUITABLE FOR

- Centralized water net for bars and kitchens

PRODUCT CODE:

- L2403P Coupling 1"G
- L2405P Coupling 3/4"G

LITRES OF SOFT WATER BASED ON WATER HARDNESS						
°f	20	30	40	50	60	Cyclic Capacity m ³ .°f
°d	11	16	22	28	33	
ppm CaCO ₃	200	300	400	500	600	
L24P	5040	3360	2520	2016	1680	100.8

