

L24PV PERFORMA VOLUMETRIC AUTOMATIC WATER SOFTENER



AUTOTROL VALVE
268/760 LOGIX



WATER CONNECTION
3/4" G - 1" G



MIXER



WATER CONNECTION
3/4" G - 1" G

**VOLUMETRIC
TURBINE**



TECNICAL FEATURES

Weight		22 kg
Power supply		230V50/60 Hz
	optional	120V 60 Hz
Max flow rate suggested		4000 l/h
Water connection		3/4" G - 1" G
Salt quantity for regeneration cycle		2.7 kg
Room temperature		min 4°C – max 35°C
Salt refill		75 kg

INFEEED WATER FEATURES

Drinkable water	
Clear water (SDI 1)	
Temperature	Min 6° C Max 25°C
Infed water pressure	Min 2 bar Max 8 bar
Max water hardness	90°f

THE SOFTENER IS COMPOSED OF

- 1 Brine tank 100 litres
- 1 268/760 Logix Autotrol Valve
- 1 Vessel 8" x 35" with 16.8 litres cationic resins adapt for softening
- 1 Instruction manual
- 4 Metres of unloading pipe
- 1 Overflow curved union joint
- 1 Drain connection
- 1 Resin disinfection kit (OPTIONAL)

THE SOFTENER IS SUITABLE FOR

- Centralized water net for bars and kitchens

PRODUCT CODE:

- L2433P Coupling 1" G
- L2455P Coupling 3/4" G

LITRES OF SOFT WATER BASED ON WATER HARDNESS						
°f	20	30	40	50	60	Cyclic Capacity m ³ .°f
°d	11	16	22	28	33	
ppm CaCO ₃	200	300	400	500	600	
L24PV	5040	3360	2520	2016	1680	100.8

