

L32PV PERFORMA VOLUMETRIC AUTOMATIC WATER SOFTENER



**AUTOTROL VALVE
268/760 LOGIX**



**WATER CONNECTION
3/4" G - 1" G**



MIXER



**WATER CONNECTION
3/4" G - 1" G**

**VOLUMETRIC
TURBINE**



DIA.219

DIA.480

TECNICAL FEATURES

Weight		27 kg
Power supply		230V50/60 Hz
	optional	120V 60 Hz
Max flow rate suggested		4000 l/h
Water connection		3/4G"-1"G
Salt quantity for regeneration cycle		4.2 kg
Room temperature		min 4°C – max 35°C
Salt refill		75 kg

INFEEED WATER FEATURES

Drinkable water	
Clear water (SDI 1)	
Temperature	Min 6° C Max 25°C
Infed water pressure	Min 2 bar Max 8 bar
Max water hardness	90°f

THE SOFTENER IS COMPOSED OF

- 1 Brine tank 100 litres
- 1 268/760 Logix Autotrol Valve
- 1 Vessel 8" x 44" with 22.4 litres cationic resins adapt for softening
- 1 Instruction manual
- 4 Metres of unloading pipe
- 1 Overflow curved union joint
- 1 Drain connection
- 1 Resin disinfection kit (OPTIONAL)

THE SOFTENER IS SUITABLE FOR

- Centralized water net for bars and kitchens

PRODUCT CODE:

- L3233P Coupling 1"G
- L3255P Coupling 3/4"G

LITRES OF SOFT WATER BASED ON WATER HARDNESS						
°f	20	30	40	50	60	Cyclic Capacity m ³ .°f
°d	11	16	22	28	33	
ppm CaCO ₃	200	300	400	500	600	
L32PV	6720	4480	3360	2688	2240	134.4

