

## L38PV PERFORMA VOLUMETRIC AUTOMATIC WATER SOFTENER



### TECNICAL FEATURES

Weight		33 kg
Power supply		230V50/60 Hz
	optional	120V 60 Hz
Max flow rate suggested		4000 l/h
Water connection		3/4" G - 1" G
Salt quantity for regeneration cycle		5.6 kg
Room temperature		min 4°C – max 35°C
Salt refill		75 kg

### INFEEED WATER FEATURES

Drinkable water	
Clear water (SDI 1)	
Temperature	Min 6° C Max 25°C
Infed water pressure	Min 2 bar Max 8 bar
Max water hardness	90°f

### THE SOFTENER IS COMPOSED OF

- 1 Brine tank 100 litres
- 1 268/760 Logix Autotrol Valve
- 1 Vessel 10" x 35" with 26.6 litres cationic resins adapt for softening
- 1 Instruction manual
- 4 Metres of unloading pipe
- 1 Overflow curved union joint
- 1 Drain connection
- 1 Resin disinfection kit (OPTIONAL)

### THE SOFTENER IS SUITABLE FOR

- Centralized water net for bars and kitchens

### PRODUCT CODE:

- L3833P Coupling 1" G
- L3855P Coupling 3/4" G

LITRES OF SOFT WATER BASED ON WATER HARDNESS						
°f	20	30	40	50	60	Cyclic Capacity m <sup>3</sup> .°f
°d	11	16	22	28	33	
ppm CaCO <sub>3</sub>	200	300	400	500	600	
<b>L38PV</b>	<b>7980</b>	<b>5320</b>	<b>3990</b>	<b>3192</b>	<b>2660</b>	<b>159.6</b>

