

L62PV PERFORMA VOLUMETRIC AUTOMATIC WATER SOFTENER



TECNICAL FEATURES

Weight		48 kg
Power supply		230V50/60 Hz
	optional	120V 60 Hz
Max flow rate suggested		4000 l/h
Water connection		3/4" G - 1" G
Salt quantity for regeneration cycle		9.5 kg
Room temperature		min 4°C – max 35°C
Salt refill		100 kg

INFEEED WATER FEATURES

Drinkable water	
Clear water (SDI 1)	
Temperature	Min 6° C Max 25°C
Infed water pressure	Min 2 bar Max 8 bar
Max water hardness	90°f

THE SOFTENER IS COMPOSED OF

- 1 Brine tank 150 litres
- 1 268/760 Logix Autotrol Valve
- 1 Vessel 10" x 54" with 43.4 litres cationic resins adapt for softening
- 1 Instruction manual
- 4 Metres of unloading pipe
- 1 Overflow curved union joint
- 1 Drain connection
- 1 Resin disinfection kit (OPTIONAL)

THE SOFTENER IS SUITABLE FOR

- Centralized water net for bars and kitchens

PRODUCT CODE:

- L6233P Coupling 1" G
- L6255P Coupling 3/4" G

LITRES OF SOFT WATER BASED ON WATER HARDNESS						
°f	20	30	40	50	60	Cyclic Capacity m ³ .°f
°d	11	16	22	28	33	
ppm CaCO ₃	200	300	400	500	600	
L62PV	13020	8680	6510	5208	4340	260.4

