


ER16 WATER SOFTENER

The **ER16** softener features a cationic resin to soften water. Used with the **ERV** valve, it supplies water to the connected equipment. Softener replacement is needed when the supplied water is no more soft water due to resin depletion (see table). Thanks to the ERA equipment, the softener is regenerated so as to be used again. Replacement and regeneration procedures are nice and smoothly carried out; furthermore, they do not require disrupting water supply to the connected devices.



TECHNICAL FEATURES

Height	mm 770
Weight	kg 15
Infeed water pressure	Min 2 bar Max 6bar
Max flow rate suggested	800 l/h
Room temperature	Min 4°C Max 35°C
Salt quantity for regeneration cycle	2 kg

INFEED WATER FEATURES

Drinkable water	
Temperature	Min 6°C Max 25°C
Clear water	
Max water hardness	90°f

THE VALVE PACKAGE CONTAINS

- 1 ERV Valve
- 1 Instruction manual
- 1 Unloading pipe
- 2 Coupling 3/8\"/>

THE PACKAGING OF CYLINDER CONTAINS:

- 1 Vessel 16 litres inox with 10.99 litres cationic resins adapt for softening
- 1 Instruction manual

PRODUCT CODE: ER16

LITRES OF SOFT WATER BASED ON WATER HARDNESS

WATER HARDNESS	20°f	30°f	40°f
	11°d	16°d	22°d
	200PpmCaCo ³	300PpmCaCo ³	100PpmCaCo ³
	Litres H ₂ O	coffee	tè
Modell ER16	3360	100800	33600
	2240	67200	22400
	1680	50400	16800

