

## ER16 WATER SOFTENER



The **ER16** softener features a cationic resin to soften water. Used with the **ERV** valve, it supplies water to the connected equipment. Softener replacement is needed when the supplied water is no more soft water due to resin depletion (see table). Thanks to the ERA equipment, the softener is regenerated so as to be used again. Replacement and regeneration procedures are nice and smoothly carried out; furthermore, they do not require disrupting water supply to the connected devices.



### TECNICAL FEATURES

Height	mm 770
Weight	kg 15
Infeed water pressure	Min 2 bar Max 6bar
Max flow rate suggested	800 l/h
Room temperature	Min 4°C Max 35°C
Salt quantity for regeneration cycle	2 kg

### INFEED WATER FEATURES

Drinkable water	
Temperature	Min 6°C Max 25°C
Clear water	
Max water hardness	90°f

### THE VALVE PACKAGE CONTAINS

- 1 ERV Valve
- 1 Instruction manual
- 1 Unloading pipe
- 2 Coupling 3/8\"G or 3/4\"G
- 1 Inlet tap 3/8\"G or 3/4\"G

### THE PACKAGING OF CYLINDER CONTAINS:

- 1 Vessel 16 litres inox with 10.99 litres cationic resins adapt for softening
- 1 Instruction manual

### PRODUCT CODE: ER16

#### LITRES OF SOFT WATER BASED ON WATER HARDNESS

WATER HARDNESS	20°f 11°d 200PpmCaCo3	30°f 16°d 300PpmCaCo3	40°f 22°d 100PpmCaCo3
	Litres H <sub>2</sub> O coffee tè	Litres H <sub>2</sub> O coffee tè	Litres H <sub>2</sub> O coffee tè
Modell ER16	3360 100800 33600	2240 67200 22400	1680 50400 16800

