

ER5 WATER SOFTENER

The **ER5** softener features a cationic resin to soften water. Used with the **ERV** valve, it supplies water to the connected equipment. Softener replacement is needed when the supplied water is no more soft water due to resin depletion (see table). Thanks to the ERA equipment, the softener is regenerated so as to be used again. Replacement and regeneration procedures are nice and smoothly carried out; furthermore, they do not require disrupting water supply to the connected devices.



TECNICAL FEATURES

Height	mm 370
Weight	kg 5
Infeed water pressure	Min 2 bar Max 6bar
Max flow rate suggested	800 l/h
Room temperature	Min 4°C Max 35°C
Salt quantity for regeneration cycle	0.6 kg

INFEED WATER FEATURES

Drinkable water	
Temperature	Min 6°C Max 25°C
Clear water	
Max water hardness	90°f

THE VALVE PACKAGE CONTAINS

- 1 ERV Valve
- 1 Instruction manual
- 1 Unloading pipe
- 2 Coupling 3/8"G or 3/4"G
- 1 Inlet tap 3/8"G or 3/4"G

THE PACKAGING OF CYLINDER CONTAINS:

- 1 Vessel 5 litres inox with 3.85 litres cationic resins adapt for softening
- 1 Instruction manual

PRODUCT CODE: ER5

LITRES OF SOFT WATER BASED ON WATER HARDNESS

WATER HARDNESS	20°f 11°d 200PpmCaCo3			30°f 16°d 300PpmCaCo3			40°f 22°d 100PpmCaCo3		
	Litres H ₂ O	coffee	tè	Litres H ₂ O	coffee	tè	Litres H ₂ O	coffee	tè
Modell ER5	1050	31500	10500	700	21000	7000	525	15750	5250

