

Automatic water softener AL12 Chronometric

TECHNICAL FEATURES

Weight	15 kg
Power supply	230V 50/60 Hz
	optional 120V 60 Hz
Max flow rate suggested	1400 l/h
Room temperature	4°C – 35°C
Absorbet power	4 W
Salt quantity for regeneration cycle	1.5 kg
Salt refill	25 kg

THE PACKAGING CONTAINS

- 1 Alia Chronometric Valve
- 1 Brine tank
- 1 Vessel da 12 litres inox with 9 litres cationic resins adapt for softening
- 1 Instruction manual
- 3 Metres of unloading pipe
- 1 Overflow curved union joint
- 1 Metres of overflow pipe

CHARACTERISTIC OF FEED WATER

Feed water must be:
 Drinkable and clean (SDI 1)
 Temperature must be between 6°C and 25°C
 Pressure of feed water 0,2 ÷ 0,8 Mpa (2÷8 bar)
 Hardness must be below 900 ppm CaCO₃ (90°f)

AVAILABLE VERSIONS

- With "SALT ALARM"
- With "SALT ALARM" and ANTI-OVERFLOW



LITRES OF SOFT WATER BASED ON WATER HARDNESS						
°f	20	30	40	50	60	Cyclic Capacity m ³ .°f
°d	11	16	22	28	33	
ppm CaCO ₃	200	300	400	500	600	
AL12	2520	1680	1260	1008	840	50.4



With “**SALT ALARM**”

Code:

ABL07 AUTOMATIC WATER SOFTENER AL12 3/4”G

ABL08 AUTOMATIC WATER SOFTENER AL12 3/8”G



With “**SALT ALARM**” and **ANTI-OVERFLOW**

Code:

ABL07G AUTOMATIC WATER SOFTENER AL12 3/4”G NG

ABL08G AUTOMATIC WATER SOFTENER AL12 3/8”G NG

