

L50V 255 LOGIX VOLUMETRIC AUTOMATIC WATER SOFTENER



TECNICAL FEATURES

| | | |
|--------------------------------------|----------|--------------------|
| Weight | | 40 kg |
| Power supply | | 230V50/60 Hz |
| | optional | 120V 60 Hz |
| Max flow rate suggested | | 1500 l/h |
| Water connections | | 3/4" G Mix |
| Salt quantity for regeneration cycle | | 7.2 kg |
| Room temperature | | min 4°C – max 35°C |
| Salt refill | | 100 kg |

INFEEED WATER FEATURES

| | |
|-----------------------|--------------------|
| Drinkable water | |
| Temperature | Min 6°C Max 25°C |
| Infeed water pressure | Min 2bar Max 8 bar |
| Clear water | (SDI 1) |
| Max water hardness | 90°f |

THE SOFTENER IS COMPOSED OF

- 1 Brine tank 150 litres
- 1 255/760 Logix Autotrol Valve
- 1 Vessel 10" x 44" with 35 litres cationic resins adapt for softening
- 1 Instruction manual
- 4 Metres of unloading pipe
- 1 Overflow curved union joint
- 1 Drain connection
- 1 Resin disinfection kit (OPTIONAL)

THE SOFTENER IS SUITABLE FOR

- Centralized water net for bars and kitchens

PRODUCT CODE

L5055 Coupling 3/4" G

| LITRES OF SOFT WATER BASED ON WATER HARDNESS | | | | | | |
|----------------------------------------------|-------|------|------|------|------|---------------------------------------|
| °f | 20 | 30 | 40 | 50 | 60 | Cyclic Capacity m ³ .°f |
| °d | 11 | 16 | 22 | 28 | 33 | |
| ppm CaCO ₃ | 200 | 300 | 400 | 500 | 600 | |
| L50V | 10500 | 7000 | 5250 | 4200 | 3500 | 210 |

