

## L24 255 LOGIX CHRONOMETRIC AUTOMATIC WATER SOFTENER



### TECNICAL FEATURES

Weight		22 kg
Power supply		230V50/60 Hz
	optional	120V 60 Hz
Max flow rate suggested		1500 l/h
Water connections		3/4" G Mix
Salt quantity for regeneration cycle		2.7 kg
Room temperature		min 4°C – max 35°C
Salt refill		75 kg

### INFEEED WATER FEATURES

Drinkable water	
Temperature	Min 6°C Max 25°C
Infeed water pressure	Min 2bar Max 8 bar
Clear water	(SDI 1)
Max water hardness	90°f

### THE SOFTENER IS COMPOSED OF

- 1 Brine tank 100 litres
- 1 255/740 Logix Autotrol Valve
- 1 Vessel 8" x 35" with 16.8 litres cationic resins adapt for softening
- 1 Instruction manual
- 4 Metres of unloading pipe
- 1 Overflow curved union joint
- 1 Drain connection
- 1 Resin disinfection kit (OPTIONAL)

### THE SOFTENER IS SUITABLE FOR

- Centralized water net for bars and kitchens

### PRODUCT CODE

L2405 Coupling 3/4" G

LITRES OF SOFT WATER BASED ON WATER HARDNESS							Cyclic Capacity m <sup>3</sup> .°f
°f	20	30	40	50	60		
°d	11	16	22	28	33		
ppm CaCO <sub>3</sub>	200	300	400	500	600		
<b>L24</b>	<b>5040</b>	<b>3360</b>	<b>2520</b>	<b>2016</b>	<b>1680</b>	<b>100.8</b>	

