

## **AUTOMATIC WATER SOFTENERS GIX SERIES**

GIX5, GIX8 RC, GIX12 form the GIX series of automatic water softeners equipped with the LOGIX valve in the chronometric and volumetric versions. The LOGIX valve stands out for its excellent mechanical qualities which make it robust and reliable.

The GIX8 RC model comes with a new fairing that protects from dust and foreign bodies. The wide lid opening makes it easier to insert salt into the brine tank and protects the upper part of the softener from possible impacts. The water softener cover remains attached to the salt container when opening.

They are simple to install and program, they are very reliable and have low operating costs. Once programmed they are completely autonomous in their functions.



The GIX series consist of the following chronometric and volumetric models:

GIX5 – GIX8 RC – GIX12  
GIX5V – GIX8V RC – GIX12V

LITRES OF SOFTENED WATER BASED ON HARDNESS						
°f	20	30	40	50	60	Cyclic Capacity m <sup>3</sup> ·°f
°d	11	16	22	28	33	
ppm CaCO <sub>3</sub>	200	300	400	500	600	
<b>GIX5 - GIX5V</b>	1050	700	525	420	350	21.0
<b>GIX8 RC - GIX8V RC</b>	1680	1120	840	672	560	33.6
<b>GIX12 - GIX12V</b>	2520	1680	1260	1008	840	50.4

Model	GIX5	GIX8 RC	GIX12
Total height h	515	540	650
Weight Kg	11	12	15
Capacity	5	12	16
Resin volume	5.6	8,4	11,2
Salt per regeneration	1.0 Kg	1.5 Kg	2.0 Kg



### TECHNICAL FEATURE

Infeed water pressure	0.1 – 0.8 MPa (1-8 bar)
Nominal flow rate	1500 l/h
Room temperature	4°C – 35°C
Water pipe connections	1/2" G (F) o 3/4" G (F) with mixer



Water connection

### INFEEED WATER EATURES

Infeed water must be:

- Drinkable and clear
- Its temperature shall range from 6°C to 25°C
- Water hardness shall be lower than 900 ppm CaCO<sub>3</sub> (90 °f)

## THE SOFTENER IS SUITABLE FOR

Coffee machines  
Glass washers and dishwashers  
Professional ovens  
Ice makers



For additional information please contact us at [info@devecchigaetano.com](mailto:info@devecchigaetano.com)

## HYGIENIC SAFETY NORMS AND ICIM TESTING

This equipment has been tested by the ICIM S.p.a., the Italian Certification Institute for Mechanic, as its licensed laboratory, in order to certify its compliance with the following regulations:

- **Reg. n.1935/2004/CE** products and components in contact with elements according to the dispositions MOCA.
- **D.M. n.174/2004** products and components utilised in contact with feed water.

It is **MANDATORY** to use original replacements for repairs and maintenance, in order to guarantee hygienic safety and product performance.



**ORDERING CODES:**

**CHRONOMETRIC GIX Series**

**ACX02A** = WATER SOFTENER GIX5 1/2"G AC  
**ACX05A** = WATER SOFTENER GIX5 3/4"G MIX AC  
**ABX02A** = WATER SOFTENER GIX12 1/2"G AC  
**ABX05A** = WATER SOFTENER GIX12 3/4"G MIX AC

**CHRONOMETRIC GIX Series with "ANTI-OVERFLOW DEVICE"**

**ACX02AG** = WATER SOFTENER GIX5 1/2"G AC NG  
**ACX05AG** = WATER SOFTENER GIX5 3/4"G MIX AC NG  
**ARX02** = WATER SOFTENER GIX8 RC 1/2"G AC  
**ARX05** = WATER SOFTENER GIX8 RC 3/4"G MIX AC  
**ABX02AG** = WATER SOFTENER GIX12 1/2"G AC NG  
**ABX05AG** = WATER SOFTENER GIX12 3/4"G MIX AC NG

**VOLUMETRIC GIX Series**

**ACX22A** = WATER SOFTENER GIX5V 1/2"G AC  
**ACX55A** = WATER SOFTENER GIX5V 3/4"G MIX AC  
**ABX22A** = WATER SOFTENER GIX12V 1/2"G AC  
**ABX55A** = WATER SOFTENER GIX12V 3/4"G MIX AC

**VOLUMETRIC GIX Series with "ANTI-OVERFLOW DEVICE"**

**ACX22AG** = WATER SOFTENER GIX5V 1/2"G AC NG  
**ACX55AG** = WATER SOFTENER GIX5V 3/4"G MIX AC NG  
**ARX22** = WATER SOFTENER GIX8V RC 1/2"G AC  
**ARX55** = WATER SOFTENER GIX8V RC 3/4"G MIX AC  
**ABX22AG** = WATER SOFTENER GIX12V 1/2"G AC NG  
**ABX55AG** = WATER SOFTENER GIX12V 3/4"G MIX AC NG